

# K-600

## Multi-gas Detector with pump for O2

### FEATURES

- Advanced MCU for Low-Power Consumption
- LCD display
- Self-Test Function
- Adjustable alarms
- Two Instant Alarm Points
- Audio, Visual LED and Vibratory Indicators
- Three buttons Operation for Simple Use
- Strong, Durable Rubber Casing Provides Anti-Slip Handleability
- 500pcs alarming record data logger
- Can be connected with computer Module monitoring, Sensor setup, Alarm record
- Colorful LCD gas curve display
- Available for CO, H2S, O2 and combustible gas
- Rechargeable
- 1 years warranty
- ATEX approval

### SPECIFICATIONS

#### Range:

**O2:** 0-30% by Volume

#### Alarm Point:

**O2:** 19.5 by Vol. decreasing and 23.5% by Vol. increasing

#### Method of Detection:

Diffusion

**Sensor:** CO, H2S and O2-Electrochemical

Combustible Gases-Catalytic

**Display:** 2.4 inch colored LCD

**Temperature:** -20°C~60°C

**Humidity:** 5 to 95% RH, non-condensing

**Power:** 3.7VDC 3600mA rechargeable lithium battery

**Operating time:** Approximately 15 hours Continuous, non-alarm conditions

**Charge Time:** 4-6 hours

**Dimensions:** 174mm\*68mm\*47mm

**Sound:** 85 dB at 1m

**Weight:** 210g

**Ingress Protection:** IP65

